D=480 mm

W=500 mm

•Contents of this catalog are as of June 28, 2021

Image Display


Image Adjustment

H=1,200 mm

FRONT

SIDE

**BACK** 



Beam Focus Method Full Digital Method

4 Stages Dynamic Transmission Focus Dynamic Receiving Focus

Ultrasound Frequency Rate 2.8~11.0 MHz Display Monitor 12.1inch Color Liquid Crystal

> Wide range viewing angle (Horizontal: 170° Vertical: 170°)

Up/Down, Left/Right B-Gain, M-Gain: 36~100 dB 1 dB step

Dynamic Range: 35~95 dB 10 dB step (1 dB adjustable)

STC: 8-Level Side Control 20~100% (10% step) Acoustic Power:

5 styles ycorrection:

H-res(Image Enhancement): OFF, Detail1, Detail2,

Mild, Detail3, Resolution, Penetration, Clarity, Boundary, Anatomy

Sweep Speed (M-Mode ): Doppler CFM(Color Flow Mapping), PD (Power Doppler)

PW(Pulse Wave Doppler)

Display Area for Doppler Vertical, Box 255 frames Cine Memory

Measurement Function Distance, Circumference, Area, Volume, Hip Joint, Histogram, Pregnancy week, Velocity, LV Calculation

Character Display Hospital Name(40), Patient Name(30), ID(26), Age, Sex, DOB, Date, Time, Probe Type, Range, Gain,

> MI/TI Value, Doppler Gain, Doppler Speed Range, ROI Acoustic Power, Frequency, Dynamic Range, Gamma, H-res, Gray Scale, Focus Information

Probe Connector 500 mm(W) x 1,200 mm(H) x 480 mm(D) Dimension

Net Weight AC Adapter 100~240 V 50/60 Hz Power Source

Data Storage Still Image(JPEG)

Internal(100 image max.) / External USB memory

Still Image(DICOM) External USB memory External USB memory Moving Image(AVI)

External I/O USB Memory Port Video Output Foot Switch Port

Printer Remote Port x 1 Probes Linear Probe (11.0/9.0/6.0 MHz 40 mm) HLS-594M

> (10.0/7.5/5.0 MHz 50 mm) HLS-575M Convex Probe (5.0/3.5/2.8 MHz 60 R) HCS-436M

(5.0/3.5/2.8 MHz 60 R) HCS-436MSC Micro-Convex Probe

(9.0/7.5/5.0 MHz 20 R) HCS-572M

Transvaginal probe

(9.0/7.5/5.0 MHz 10 R) HCS-4710MV

AC Adapter, Power Cord, Ultrasound Gel

•The specification and appearance are subject to change without notice for improvement. •Actual colors of products and colors of this catalog may a little different cause of printing. HONDA ELECTRONICS CO.,LTD.

Medical Division

20 Oyamazuka, Oiwa-cho, Toyohashi Aichi 441-3193 Japan TEL: +81-532-41-2514 FAX: +81-532-41-4441 www.honda-el.net

Registered company for ISO9001/ISO13485/ISO14001

is the trademark of HONDA ELECTRONICS CO.,LTD. This catalog is printed by vegetable ink on recycle paper.

HONDA ELECTRONICS CO.,LTD.



DIAGNOSTIC SCANNER **Convex / Linear Ultrasonic System** 

**HS-2700** 

**12.1**inch






## **Probes**

In order to deal with wide range application, more high resolution probes have been added to our selection. Please select the best matching probe for your needs.

40 mm) (2.2 m)

(20R) (2 m)










\*Video printer is not included.

## Doppler Mode

HS-2700 supports CFM (Color Flow Mapping), PD (Power Doppler) and PW(Pulse Wave Doppler) modes. They will adapt to a wide range of medical application.

Additionally, HS-2700 has two kinds of ROI types. (Box, Vertical)








PD (Power Doppler)



PW (Pulse Wave Doppler)









 $\mathcal{H}$ -res (Our Resolution Technology)

The development of ultrasound technology over the years crystallized into the image enhancing technology as "H-res". Optimum image can be achieved by adjusting the H-res parameter for each application and probe.







## **Main applications**

- OB/GYN diagnosis
- Abdominal diagnosis
- Thyroid, Accessory thyroid, Carotid, and Cervical
- Musculoskeletal diagnosis

## Made in Japan

This product is assembled in Japan, We produce even the ultrasound sensor ceramics in its own factory.

